

09/848,004

**IN THE CLAIMS**

Cancel claims 49 and 50.

Amend claims 48, 51, 52, 53, 55, 56, and 57 as follows:

Add new claims 58-61 as follows:

1-47. (canceled)

48. (currently amended) A check processing apparatus comprising:

an image capture transport including (i) an image capture device for capturing images of physical checks, (ii) a number of pockets into which physical check can be sorted, and (iii) a transport controller for providing information relating to physical checks which have been processed at the image capture transport;

~~a balancing station including (i) a display for displaying check images, (ii) an input device for enabling an operator to enter check amounts, and (iii) a balancing station controller for examining information associated with check images to determine if a balanced condition exists and for providing a balance complete signal when a determination is made that a balanced condition exists;~~

an encoding transport including a magnetic ink character recognition (MICR) encoder for encoding MICR codelines onto physical checks;

a physical receptacle for (i) containing physical checks which have been processed at the image capture transport, and (ii) allowing the physical receptacle along with physical checks contained therein to be physically transported from the image capture transport to an encoding transport;

an electronic label affixed to the physical receptacle and including (i) a physical display for displaying a visual message, (ii) a first communication interface for receiving electronic messages which have been wirelessly transmitted from another communication interface, and (iii) a processor for causing the physical display to display a

09/848,004

visual message to provide an operator with information which relates to at least some of the physical checks contained in the physical receptacle;

a subserver for (i) receiving information which associates the physical receptacle and the electronic label affixed thereto to a corresponding pocket of the image capture transport, and (ii) ~~receiving the balance complete signal from the balancing station;~~

a transmitter server for generating display messages based upon information from the subserver; and

a second communication interface for wirelessly transmitting the generated display messages from the transmitter server to the first communication interface of electronic label so that visual information relating to at least some of the physical checks contained in the physical receptacle can be displayed on the physical display of the electronic label.

49. (canceled)

50. (canceled)

51. (currently amended) A check processing apparatus according to claim 48, wherein the electronic label includes a first manually-operable button electrically coupled to the processor and for, when manually operated, directs directing the processor to cause the physical display to display information in sequential screens.

52. (currently amended) A check processing apparatus according to claim 51, wherein the electronic label includes a second manually-operable button electrically coupled to the processor and for, when manually operated, allows allowing an operator to send a signal to the second communication interface.

09/848,004

53. (currently amended) A check processing apparatus according to claim 48, wherein the electronic label further includes an alerter electronically coupled to the processor and for, when being driven by the processor, provides providing an audible alert signal.

54. (previously presented) A check processing apparatus comprising:

- an image capture transport including (i) an image capture device for capturing images of physical checks, (ii) a number of pockets into which physical check can be sorted, and (iii) a transport controller for providing information relating to physical checks which have been processed at the image capture transport;
- a balancing station including (i) a display for displaying check images, (ii) an input device for enabling an operator to enter check amounts, and (iii) a balancing station controller for examining information associated with check images to determine if a balanced condition exists and for providing a balance complete signal when a determination is made that a balanced condition exists;
- a reconciliation station including (i) a display for displaying check images, and (ii) a reconciliation station controller for reconciling physical checks which have been identified as being exception items and for providing a reconciliation complete signal when reconciliation is completed;
- an encoding transport including a magnetic ink character recognition (MICR) encoder for encoding MICR codelines onto physical checks;
- a physical receptacle for (i) containing physical checks which have been processed at the image capture transport, and (ii) allowing the physical receptacle along with physical checks contained therein to be physically transported from the image capture transport to the encoding transport;
- an electronic label affixed to the physical receptacle and including (i) a physical display for displaying a visual message, (ii) a first communication interface for receiving electronic messages which have been wirelessly transmitted from another communication interface, and (iii) a processor for causing the physical display to display a

09/848,004

visual message to provide an operator with information which relates to at least some of the physical checks contained in the physical receptacle;

a subserver for (i) receiving information which associates the physical receptacle and the electronic label affixed thereto to a corresponding pocket of the image capture transport, (ii) receiving the balance complete signal from the balancing station, and (iii) receiving the reconciliation complete signal from the reconciliation station controller;

a transmitter server for generating display messages based upon information from the subserver; and

a second communication interface for wirelessly transmitting the generated display messages from the transmitter server to the first communication interface of electronic label so that visual information relating to at least some of the physical checks contained in the physical receptacle can be displayed on the physical display of the electronic label.

55. (currently amended) A check processing apparatus according to claim 54, wherein the electronic label includes a first manually-operable button electrically coupled to the processor and for, when manually operated, ~~directs~~ directing the processor to cause the physical display to display information in sequential screens.

56. (currently amended) A check processing apparatus according to claim 55, wherein the electronic label includes a second manually-operable button electrically coupled to the processor and for, when manually operated, ~~allows~~ allowing an operator to send a signal to the second communication interface.

57. (currently amended) A check processing apparatus according to claim 54, wherein the electronic label further includes an alerter electronically coupled to the processor and for, when being driven by the processor, ~~provides~~ providing an audible alert signal.

09/848,004

58. (new) A check processing apparatus for enabling an operator to physically transport checks from an image capture transport which captures images of checks and sorts the checks into a plurality of pockets to an encoding transport which encodes magnetic ink character recognition (MICR) codelines onto checks, the check processing apparatus comprising:

a plurality of check document trays for (i) containing checks which have been sorted into the plurality of pockets at the image capture transport, (ii) allowing checks to be moved from each of the plurality of pockets into a corresponding one of the plurality of check document trays, and (iii) allowing the plurality of check document trays along with checks contained therein to be physically transported from the image capture transport to the encoding transport for encoding MICR codelines onto the checks; and

a plurality of electronic labels associated with the plurality of check document trays such that each of the plurality of electronic labels is affixed to a corresponding one of the plurality of check document trays, each of the plurality of electronic labels including (i) a physical display for displaying a visual message, (ii) a communication interface for receiving electronic messages which have been wirelessly transmitted from a communication interface associated with the image capture transport, and (iii) a processor for causing the physical display to display a visual message which is based upon at least one electronic message which has been received from the communication interface associated with the image capture transport to provide visual information which relates to at least some checks contained in a check document tray which has been physically transported from the image capture transport to the encoding transport.

59. (new) A check processing apparatus according to claim 58, wherein the electronic label includes a first manually-operable button electrically coupled to the processor and for, when manually operated, directing the processor to cause the physical display to display information in sequential screens.

60. (new) A check processing apparatus according to claim 59, wherein the

09/848,004

electronic label includes a second manually-operable button electrically coupled to the processor and for, when manually operated, allowing an operator to send a signal to the communication interface associated with the image capture transport.

61. (new) A check processing apparatus according to claim 58, wherein the electronic label further includes an alerter electronically coupled to the processor and for, when being driven by the processor, providing an audible alert signal.